

Flex 72 RGB

RGB LED strip Suri



Flex 72 RGB

MEDIDAS	1,000 x 6 x 1.4 mm (segment 42 mm) 39.4 x 0.24 x 0.06 in (segment 1.65 in)
VOLTAGE	12V
POWER CONS	16,3 W (max.)
LED	Nichia SMD 227 (Full color LED)
LED QUANT.	72 LED/m (24 segments of 3 LED)
LED COLOR	B 466 / G 536 / R 625 nm
LUMEN	B 36lm/m / G 321 lm/m / R 196 lm/m
LUMEN EFF.	36,62 lm/W
LIGHT BEAM	120°
MILICANDELA	B 150mcd/LED / G 1400mcd/LED / R 850mcd/LED
LIFE SPAN	>56.000 Hours
T_p MAX.	65°C
% FAILURES	Category F 10
LUMINOUS FLUX	Category B L70
CHROM. COOR.	B X=0,136 Y=0,051 G X=0,220 Y=0,723 R X=0,700 Y=0,298
PCB	Flexible copper (>75 microns)



All rights reserved. The information in this document is subject to change without notice.
Manufactured in our installations in Barcelona, Spain.

C/ Josefina Vidal Folch 1-3, 08930 Barcelona (+34) 935 334 600 - www.actilum.com

Actilum Lux