


Line Ledexpert

Profile Ledexpert



Line Ledexpert 112

MEASURES Up to 2,500x18x9.5 mm
VOLTAGE 24 V
POWER CONS. 15 W/m

LED COLOR	3,000K	4,000K	5,000K
LUMEN	1,668 lm/m	2,131 lm/m	2,241 lm/m
LIGHT EFFIC.	107 lm/W	135 lm/W	145 lm/W
CRI	> 85%		

LIFE SPAN > 36,000 Hours
OPERAT. TEMP. 36.9°C
% FAILURES Category F10
LUMINOUS FLUX Category B L70
COORD. CROM. 5-step MacAdam Ellipse

Line Ledexpert 126

MEASURES Up to 2,500x18x9.5 mm
VOLTAGE 24 V
POWER CONS. 10 W/m

LED COLOR	3,000 / 4,000 / 5,000 / 6,000 K
LUMEN	1,000 lm/m
LIGHT EFFIC.	100 lm/W
CRI	> 90%

LIFE SPAN > 36,000 Hours
OPERAT. TEMP. 34.8°C
% FAILURES Category F10
LUMINOUS FLUX Category B L70
COORD. CROM. 5-step MacAdam Ellipse

Line Ledexpert 182

MEASURES Up to 2,500x18x9.5 mm
VOLTAGE 24 V
POWER CONS. 15,3 W/m

LED COLOR	3,000 / 4,000 / 5,000 / 6,000 K
LUMEN	1,540 lm/m
LIGHT EFFIC.	100 lm/W
CRI	> 90%

LIFE SPAN > 36,000 Hours
OPERAT. TEMP. 34.8°C
% FAILURES Category F10
LUMINOUS FLUX Category B L70
COORD. CROM. 5-step MacAdam Ellipse



All rights reserved. The information in this document is subject to change without notice.
 Manufactured in our installations in Barcelona, Spain.
 C/ Josefina Vidal Folch 1-3, 08930 Barcelona (+34) 935 334 600 - www.actilum.com