

# Parallel L / L+

Edge light



## L5 / L5 +

<b>MEASURES</b>	380x24x14 mm (15x0.94x0.55 in)	
<b>WEIGHT</b>	65 gr	
<b>VOLTAGE</b>	24 V	
<b>POWER CON.</b>	<b>L5</b> 14 W	<b>L5+</b> 20.5 W
<b>LED COLOR</b>	3,000/4,000/5,000/6,000 K	
<b>LUMEN</b>	<b>L5</b> ≈ 1,706 lm	<b>L5+</b> ≈ 2,123 lm
<b>LIGHT EFFIC.</b>	<b>L5</b> ≈ 120 lm/W	<b>L5+</b> ≈ 104 lm/W
<b>LIGHT BEAM</b>	10° and 42°	
<b>CRI</b>	> 80%	

## L3 / L3 +

<b>MEASURES</b>	220x24x14 mm (8.7x0.94x0.55 in)	
<b>WEIGHT</b>	40 gr	
<b>VOLTAGE</b>	24 V	
<b>POWER CON.</b>	<b>L3</b> 10 W	<b>L3+</b> 13.5 W
<b>LED COLOR</b>	3,000/4,000/5,000/6,000 K	
<b>LUMEN</b>	<b>L3</b> ≈ 1,074 lm	<b>L3+</b> ≈ 1,404 lm
<b>LIGHT EFFIC.</b>	<b>L3</b> ≈ 111 lm/W	<b>L3+</b> ≈ 104 lm/W
<b>LIGHT BEAM</b>	10° and 42°	
<b>CRI</b>	> 80%	

## L1

<b>MEASURES</b>	80x24x14 mm (3.1x0.94x0.55 in)	
<b>WEIGHT</b>	14 gr	
<b>VOLTAGE</b>	24 V	
<b>POWER CON.</b>	3.7 W	
<b>LED COLOR</b>	3,000/4,000/5,000/6,000 K	
<b>LUMEN</b>	≈ 345 lm	
<b>LIGHT EFFIC.</b>	≈ 93 lm/W	
<b>LIGHT BEAM</b>	10° and 42°	
<b>CRI</b>	> 80%	



### OTHER INFO:

<b>LIFE SPAN</b>	> 56,000 Hours
<b>T<sub>p</sub> MAX.</b>	85°C
<b>% FAILURES</b>	Category F10
<b>LUMINOUS FLUX</b>	Category A L90
<b>CHROM. COORD.</b>	Maintenance 3-step MacAdam Ellipse



All rights reserved. The information in this document is subject to change without notice.  
 Manufactured in our installations in Barcelona, Spain.  
 C/ Josefina Vidal Folch 1-3, 08930 Barcelona (+34) 935 334 600 - [www.actilum.com](http://www.actilum.com)

**Actilum** Lux